

January 6, 2006
Case No.: GP-303478 (2760/105)
Serial No.: 10/635,299
Filed: August 6, 2003
Page 2 of 13

CLAIM AMENDMENTS:

Please amend the claims as follows so that the claims currently pending read as follows, wherein no new matter has been added to the claims:

1. (Original) A method for providing real-time traffic updates to a mobile vehicle communication device comprising:
 - producing traffic incident region coordinate data;
 - communicating the traffic incident region coordinate data to a mobile vehicle communication device; and
 - determining when a traffic incident region coordinate is within a predetermined radius around the mobile vehicle communication device based on the communicated traffic incident region coordinate data.
2. (Original) The method of claim 1 wherein producing traffic incident region coordinates comprises:
 - receiving traffic incident data;
 - processing the traffic incident data to group traffic incidents into a plurality of traffic incident regions; and
 - determining a traffic incident region GPS coordinate for each of the plurality of traffic incident regions.
3. (Original) The method of claim 2 wherein the traffic incident region GPS coordinate describes the geometric center of a traffic incident region containing at least one traffic incident.

January 6, 2006
Case No.: GP-303478 (2760/105)
Serial No.: 10/635,299
Filed: August 6, 2003
Page 3 of 13

4. (Currently Amended) The method of claim 3 wherein ~~a~~ the size of the traffic incident region is controlled with a method selected from the group consisting of individually controllable, dynamically controllable, controlling depending on road density and setting the size to 10 miles or less.

5. (Original) The method of claim 3 wherein the traffic incident region has a selectable geometry.

6. (Original) The method of claim 2 wherein communicating the traffic incident region coordinate comprises:

transmitting a traffic incident region GPS coordinate for each of the plurality of traffic incident regions; and

receiving the traffic incident region GPS coordinate for each of the plurality of traffic incident regions at the mobile vehicle communication device.

7. (Original) The method of claim 6 wherein the traffic incident region GPS coordinate is transmitted via a satellite radio broadcast.

8. (Original) The method of claim 6 wherein determining when a traffic incident region is within a predetermined radius around the mobile vehicle communication device comprises:

determining a location GPS coordinate describing the location of the mobile vehicle communication device;

comparing the received traffic incident region GPS coordinate with the location GPS coordinate describing the location of the mobile vehicle communication device; and

identifying when a traffic incident region GPS coordinate is within the predetermined radius around the mobile vehicle communication device based on the comparison.

January 6, 2006
Case No.: GP-303478 (2760/105)
Serial No.: 10/635,299
Filed: August 6, 2003
Page 4 of 13

9. (Original) The method of claim 1 further comprising:
determining localized traffic incident data for the traffic incident region coordinate responsive to determining that the traffic incident region coordinate is within a forward view radius of the mobile vehicle communication device.
10. (Original) The method of claim 9 wherein determining the localized traffic incident data comprises:
initiating a communication to a service provider;
requesting the localized traffic incident data for the determined traffic incident region coordinate from the service provider;
receiving the traffic incident data for the traffic incident region coordinate from the service provider; and
providing the localized traffic incident data to a user.
11. (Original) A computer readable medium storing a computer program comprising:
computer readable code for producing traffic incident region coordinate data;
computer readable code for directing communication of the traffic incident region coordinate data to a mobile vehicle communication device; and
computer readable code for determining when a traffic incident region coordinate is within a predetermined radius around the mobile vehicle communication device based on the communicated traffic incident region coordinate data.

January 6, 2006
Case No.: GP-303478 (2760/105)
Serial No.: 10/635,299
Filed: August 6, 2003
Page 5 of 13

12. (Original) The computer readable medium of claim 11 wherein computer readable code for producing the traffic incident region coordinate comprises:

computer readable code for processing received traffic incident data to group traffic incidents into a plurality of traffic incident regions; and

computer readable code for determining a traffic incident region GPS coordinate for each of the plurality of traffic incident regions.

13. (Original) The computer readable medium of claim 12 wherein the computer readable code for determining a traffic incident region comprises code for determining a geometric center of a traffic incident region containing at least one traffic incident.

14. (Original) The computer readable medium of claim 13 wherein computer readable code for determining when a traffic incident region is within a predetermined radius around the mobile vehicle communication device comprises:

computer readable code for determining a location GPS coordinate describing the location of the mobile vehicle communication device;

computer readable code for comparing the received traffic incident region GPS coordinates with the location GPS coordinate describing the location of the mobile vehicle communication device; and

computer readable code for identifying when a traffic incident region GPS coordinate is within the predetermined radius around the mobile vehicle communication device based on the comparison.

January 6, 2006
Case No.: GP-303478 (2760/105)
Serial No.: 10/635,299
Filed: August 6, 2003
Page 6 of 13

15. (Original) The computer readable medium of claim 11 further comprising:
computer readable code for determining localized traffic incident data for the
traffic incident region coordinate responsive to determining that the traffic incident region
coordinate is within a forward view radius of the mobile vehicle communication device.

16. (Original) The method of claim 15 wherein computer readable code for
determining the localized traffic incident data comprises:
computer readable code for initiating a communication to a service provider;
computer readable code for requesting the localized traffic incident data for
the determined traffic incident region coordinate from the service provider; and
computer readable code for providing received localized traffic incident data
to a user.

17. (Original) A system for providing real-time traffic updates to a mobile vehicle
communication device comprising:
means for producing traffic incident region coordinate data;
means for communicating the traffic incident region coordinate data to a
mobile vehicle communication device; and
means for determining when a traffic incident region coordinate is within a
predetermined radius around the mobile vehicle communication device based on the
communicated traffic incident region coordinate data.

January 6, 2006
Case No.: GP-303478 (2760/105)
Serial No.: 10/635,299
Filed: August 6, 2003
Page 7 of 13

18. (Original) The system of claim 17 wherein means for producing traffic incident region coordinates comprises:
means for receiving traffic incident data;
means for processing the traffic incident data to group traffic incidents into a plurality of traffic incident regions; and
means for determining traffic incident region GPS coordinates for each of the plurality of traffic incident regions.

19. (Original) The system of claim 17 wherein means for determining when a traffic incident region is within a predetermined radius around the mobile vehicle communication device comprises:
means for determining a location GPS coordinate describing the location of the mobile vehicle communication device;
means for comparing the received traffic incident region GPS coordinates with the location GPS coordinate describing the location of the mobile vehicle communication device; and
means for identifying when a traffic incident region GPS coordinate is within the predetermined radius around the mobile vehicle communication device based on the comparison.

20. (Original) The system of claim 17 further comprising:
means for determining localized traffic incident data for the traffic incident region coordinate responsive to determining that the traffic incident region coordinate is within a forward view radius of the mobile vehicle communication device.

January 6, 2006

Case No.: GP-303478 (2760/105)

Serial No.: 10/635,299

Filed: August 6, 2003

Page 8 of 13

21. (New) A method of receiving traffic incident data at a mobile vehicle communication device in a vehicle comprising:

receiving at least one traffic incident region GPS coordinate via a satellite radio receiver at the mobile vehicle communication device;

determining whether at least one received traffic incident region GPS coordinate is within a forward view radius of the vehicle, and

initiating a communication with a call center from the mobile vehicle communication device via a wireless network based on the determination; and

receiving localized traffic incident data based on the call initiation.

22. (New) The method of claim 21 further comprising:

determining visual display support information based on the received localized traffic incident data; and

displaying the localized traffic incident data based on the determination.

23. (New) The method of claim 21 wherein the received traffic incident region GPS coordinate describes a center of a traffic incident region containing at least one traffic incident.